

# SAFETY DATA SHEET

## Bitumen Emulsion



### SECTION 1: Identification Of The Substance And Supplier

Product Name:	Bitumen Emulsion
Other Names:	Enviro Seal, Enviroplus Seal, Enviromax Seal, Dust Seal, Enviro Tack, Enviro Bind
Recommended Use:	Product is predominantly used in road making
Company Details:	Road Science
Address:	9 Owens Place, Mt Maunganui
Telephone Number:	07 575 1150
Emergency Telephone Number:	07 575 1150 24hr / 7 days or National Poisons Centre 0800 POISON (0800 764 766)
Specified Jurisdiction:	European Union
Relevant Law:	Regulation (EU) 2015/830

### SECTION 2: Hazards Identification

Hazard Statement:	No Significant Hazard
-------------------	-----------------------

### SECTION 3: Composition/Information On Ingredients

Chemical Name	Index No.	CAS No.	EC No.	Conc. (%w/w)	Classification
Amidoamine	31/03/2010	1379524-06-7	800-353-8		Skin Corr. 1B: H314; Skin Sens. 1: H317; Eye Dam. 1: H318; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;
Bitumen (Asphalt, petroleum fumes)		8052-42-4	232-490-9	50 - 80%	
Water		7732-18-5	231-791-2	20 - 40%	

## SECTION 4: First Aid Measures

---

Description of first aid measures:

**Inhalation:** May cause irritation to mucous membranes. Move the exposed person to fresh air.

**Eye contact:** Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

**Skin contact:** May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

**Ingestion:** May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

## SECTION 5: Fire-Fighting Measures

---

Extinguishing Media: Use extinguishing media appropriate to the surrounding fire conditions.

Special hazards arising from the substance or mixture: Burning produces irritating, toxic and obnoxious fumes.

Advice for firefighters: Wear suitable respiratory equipment when necessary.

## SECTION 6: Accidental Release Measures

---

Personal precautions, protective equipment and emergency procedures - Ensure adequate ventilation of the working area.

Environmental precautions – Do not allow product to enter drains. Prevent further spillage if safe.

Methods and material for containment and cleaning up – Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## SECTION 7: Handling and Storage

---

Precautions for Safe Handling: Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best

Manual Handling considerations when handling, carrying and dispensing.

Conditions for Safe Storage: Keep in a cool, dry, well ventilated area. Store in correctly labelled containers.

## SECTION 8: Exposure Control/Personal Protection

Exposure Limit Values Bitumen (Asphalt, petroleum fumes)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: WEL 8-hr limit mg/m3 total respirable dust:	WEL 8-hr limit mg/m3: 5 WEL 15 min limit mg/m3: 10 WEL 15 min limit mg/m3 total inhalable dust: -WEL 15 min limit mg/m3 total respirable dust:
Exposure controls	Appropriate engineering controls Individual protection measures Eye/face protection Skin/Hand Protection	Ensure adequate ventilation of the area. Wear protective clothing. In case of splashing, wear: approved safety goggles. PVC gauntlet gloves.

## SECTION 9: Physical and Chemical Properties

Appearance:	Liquid
Colour	Brown
Odour	Slight
Freezing Point	~ 0 °C
Initial boiling point	~ 100 °C
Flash point	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	~ 1 (H2O = 1 @ 20 °C)
Autoignition temperature	Not applicable
Explosive properties	Not applicable

## SECTION 9: Physical and Chemical Properties

Physical Appearance:	At normal room temperature these products are black rubbery solids. During use, product is heated to melting point and is a black liquid.	
Melting Point:	50 – 95°C	
Boiling Point:	Not available	
Vapour Pressure:	No data	
Vapour Density:	No data	
Water Solubility:	Insoluble	
pH:	Not applicable	
Specific Density:	1.010 – 1.033	
Flashpoint:	No data	
Flammability Limits:	LEL: 0.3%	UEL: 6.0%
Auto-ignition Temperature:	No data	

## SECTION 10: Stability and Reactivity

Reactivity: Alkalis.

Chemical stability: Stable under normal conditions.

Conditions to avoid: Do NOT allow to freeze. Protect from frost.

Incompatible materials: Alkalis.

Hazardous decomposition products: No Data Available.

## SECTION 11: Toxicological Information

Information on toxicological effects: No Significant Hazard.

## SECTION 12: Ecotoxicity Information

Toxicity

Amidoamine

Daphnia EC50/48h: 1 mg/l

Algae IC50/72h: 0.01 mg/l

## SECTION 13: Disposal Considerations

General information – Dispose of in compliance with all local and national regulations.

## SECTION 14: Transport Information

UN Number:	The product is not classified as dangerous for carriage.
UN Proper Shipping Name:	The product is not classified as dangerous for carriage.
Transport hazard class(es):	The product is not classified as dangerous for carriage.
Subsidiary Risk:	None allocated
Packing Group:	The product is not classified as dangerous for carriage.
Environmental Hazards:	The product is not classified as dangerous for carriage.
Special precautions for user	The product is not classified as dangerous for carriage.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	The product is not classified as dangerous for carriage.
Further information	The product is not classified as dangerous for carriage.

## SECTION 15: Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture:	Safety data sheets: according to Regulation (EC) No. 1907/2006 UK REGULATION Chip3: Chemical (Hazard Information and Packaging for Supply) Regulations 2002.
A chemical safety assessment	A chemical safety assessment has not been carried out..

## SECTION 16: OTHER INFORMATION

Revision Indicator:                      Issued:      1 October 2015  
   Revised:      14 May 2021

Text of Hazard Statements in Section 3:

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Eye Dam. 1: H318 - Causes serious eye damage.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Further information:

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is

The information contained in this document is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, any recommendations or suggestions which may be made are without guarantee and no warranty, expressed or implied, is given. We reserve the right to change this document at any time.