

Step 4 Clean Up



- > Clean equipment in warm soapy water only.
- > Pack and dispose of paint roller sleeve in general waste.
- > We recommend De-Solve-it (or other solvent) to clean any cured Enviro Shield.



Enviro Shield

EASY
TO
USE

Any asphalt needs waterproofing every 7-10 years when the surface oxidises.

Enviro Shield is a rejuvenation treatment that prevents cracks forming and protects against discolouration.

Versatile • Easy to Use • Long Lasting

Enviro Shield can be applied as easy as paint. It will give any surface an uplift. With a matt black finish, Enviro Shield will make the surface look like brand new asphalt.

roadscience.co.nz 0800 180 200

Step 1

Prepare



- > Remove loose material and sweep dust from the surface.
- > Make sure there is no surface water.
- > Check that there is no incoming rain for the next 4 hours.

What Do I Need?

- > Gloves (preferably latex)
- > Gumboots
- > Rags
- > Paint Roller

Mixing Quick Tips

- > Apply sand on top to add texture and increase curing time.
- > The type of sand will change the final colour of the surface.
- > Keep a lid on the bucket to prevent a skin forming.

Step 2

Application



- > Mix bucket prior to application with a stirrer.



- > Apply a light application of Enviro Shield onto surface.



- > Apply Enviro Shield and move with roller.
- > Ensure the surface is lightly coated with Enviro Shield.
- > 1 coat is enough to rejuvenate the surface.

Step 3

Drying



- > Leave product for 4 hours, do not drive over the surface during this time.



- > Add sand for more texture and faster curing.